








Choosing T5 tube retrofit adapters

T5 adapters vary hugely

Essential Features and Benefits Checklist



Feature	Benefit	✓ ClickSave	Other supplier
<p>Aluminium body</p> 	<p>Strong and light. Resists heat. Avoids 'sagging/melting plastic' common to some long 'end-cap' style adapters like this:</p> 	✓	
<p>Sole source of ClickSave T5 retrofit for 7 years, not a wholesaler.</p>	<p>Essential knowledge and project support. This gives long service, avoids issues.</p>	✓	
<p>"Pre-heat" warms tubes first</p>	<p>Longer tube life = low ongoing costs, especially if you'll use motion-sensors.</p>	✓	
<p>Choice of profiles/offsets</p> 	<p>Needed if you must fit into tight lights eg waterproof (IP65), Cat 2 / grill reflectors etc</p>	✓	
<p>'End-of-life detection' avoids failure</p>	<p>Won't try to keep 'starting' failed tube (this would stress, also waste a lot of energy)</p>	✓	
<p>Mains power only from ONE end*</p>	<p>Safer fitting/maintenance, no link end-end*</p>	✓	
<p>Reflector = more light downwards</p>  <p>so ClickSave uses less energy</p>	<p>T5 tubes can give as much light to tasks as T8 tubes if bright reflectors are used (Most 'no-reflector' adapters use much higher watts than ClickSave = wasted energy)</p>	✓	
<p>Adapter runs full length of tube so tube is powered both ends</p>	<p>Gentle start-up each tube end. Less tube wear = longer tube life.</p>	✓	
<p>6ft and 8ft adapters have two tubes</p>	<p>Illuminating full-length, not one short tube</p>	✓	
<p>Unique <i>direct-indirect</i> kit for 600x600 modular lights.</p> 	<p>'GreenCat' uses 2 x ClickSave adapters. Diffuser illuminates ceiling and walls. Calmer yet wide-awake lighting! Stops rooms feeling like 'caves'</p> <p>See 'Lighting Guide 7'</p>	✓	

Copyright ENERGY AT WORK Ltd.

More information about ClickSave advanced T5 tube adapters at www.energyatwork.co.uk
 Good lighting needs good advice. We can visit sites to help decide the best lighting method.



2012 Group Finalists

Errors and omissions excepted. All figures and specs are estimates and are pending site surveys. Any advice given is of a general nature. Some specifications of stock received may vary according to new stocks or product improvements.

* Note 2ft adapters are powered from both ends for easy fitting in modular lights